

Amendment to the Abstract:

The Abstract has been amended. A revised Abstract is attached.

The invention relates to a stuffing/dosing machine comprising a tilting hopper. The inventive machine ~~consists of~~comprises a hopper-(1) with a hermetic cover-(3) bearing a screw feeder -(14) and a narrowed base-(4) which communicates with an antechamber-(5), said antechamber communicating in turn with at least one forming chamber-(6) which is connected to an outlet-(8). Moreover, at least one actuated piston-(9) performs a stroke with one first section in the antechamber-(5) and a second section in the forming chamber-(6). First and second structural units, which are formed respectively by the aforementioned hopper-(1), cover -(3), screw feeder-(14) and narrowed base-(4) and by said antechamber-(5), forming chambers -(6), pistons-(9) and actuation means-(10), can be tilted independently between operating positions and cleaning and maintenance positions in relation to fixed frame comprising the valve-(7) and the outlet-(8).

Attachment

Respectfully submitted,

RatnerPrestia



Jacques L. Etkowicz, Reg. No. 41,738
Attorney for Applicant

JLE/kpc

Attachment: Abstract

Dated: **October 16, 2004**

P.O. Box 980
Valley Forge, PA 19482
(610) 407-0700

The Commissioner for Patents is hereby
authorized to charge payment to Deposit
Account No. **18-0350** of any fees associated
with this communication.

EXPRESS MAIL

Mailing Label Number:
Date of Deposit:

EL 983883442 US
October 18, 2004

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.



Kathleen Libby

ABSTRACT

The invention relates to a stuffing/dosing machine comprising a tilting hopper. The machine comprises a hopper with a hermetic cover bearing a screw feeder and a narrowed base which communicates with an antechamber, said antechamber communicating in turn with at least one forming chamber which is connected to an outlet. Moreover, at least one actuated piston performs a stroke with one first section in the antechamber and a second section in the forming chamber. First and second structural units, which are formed respectively by the aforementioned hopper, cover, screw feeder and narrowed base and by said antechamber, forming chambers, pistons and actuation means, can be tilted independently between operating positions and cleaning and maintenance positions in relation to fixed frame comprising the valve and the outlet.